

KEIM CONCRETAL LASUR

For masonry and concrete

FEATURES & BENEFITS

- » Lightfast, will not fade
- » Weather resistant
- » Resistant to environmental influences
- » Mineral matt finish that lasts
- » LEED - yes

FIELD OF APPLICATION

KEIM Concretal-Lasur provides a low-pigment finish on fair-faced interior and exterior concrete surfaces, e.g. to retain the fair-faced appearance. It is commonly used for changing the colour completely or simply concealing stains, wide colour variations or blending repairs with a concrete colour shade. KEIM Concretal-Lasur is also used for providing decorative colour wash finishes. KEIM Concretal-Lasur can be diluted as required with KEIM Concretal-Dilution (Fixativ) or KEIM Concretal-Base.

KEIM Concretal-Lasur can also be applied as an opaque thin-layer coatings retaining surface texture and providing protective water and weather resistant finish.

Water-proofing may be further enhanced by providing the substrate with a water-repellent pre-treatment using KEIM Silangrund or KEIM Silan-100. The application of KEIM Concretal-Lasur together with KEIM Silan-100 complies with water protection requirements as per DIN EN 1504- 2/2.2.

KEIM Concretal-Lasur is not as weather resistant on horizontal and slightly inclined surfaces.

Sol-silicate-based, thin-layer coating for providing a low pigment finish when diluted with KEIM Concretal-Dilution (Fixativ) or KEIM Concretal- Base, as well as for opaque thin-layer protective coatings. Complies with DIN EN 1504-2/2.2 when using together with KEIM Silan-100.

KEIM Concretal-Lasur protects the concrete from the action of weather and also prevents the penetration of aggressive atmospheric pollutants.

Surface textures on the concrete, such as shuttering board textures, are fully retained. The surface is mineral matt. At various dilutions with KEIM Concretal-Dilution (Fixativ) or KEIM Concretal- Base, different low-pigment finishes may be achieved or optical problems, such as stains or colour differences can be corrected.

SUBSTRATE PREPARATION

The substrate must be sound, solid, dry, clean and free of dust, grease, oils, salts, moss, algae and other substances that would prevent bonding. Old resin coatings, loose substrate layers and organically bound coats must be removed.

Repair damaged areas using the KEIM Concretal concrete repair system.

For new concrete structures; Concrete should be at least 28 days old and any formwork oil for Concrete, mold lubricating oil, shuttering oil, mold release oil, concrete form oil residues and curing compounds should be removed with KEIM Concrete Cleaner (Betonschnellreiniger) or by other methods. Clean, strong concrete without a sinter layer requires no pre-treatment.

Before KEIM Concretal-Lasur is applied, highly absorbent substrates or surfaces exposed to severe weather may be treated with a water-repellent substrate treatment using KEIM Silangrund or KEIM Silan-100 (tested to ZTV-ING) to enhance waterproofing. A subsequent base coat of KEIM Concretal-Lasur may be applied after approx. 4 hours for KEIM Silangrund and after 4 to 12 hours for KEIM Silan-100.


Soft, porous concrete surfaces or existing mineral coats may be stabilized by pre-treatment with KEIM Concretal-Dilution (Fixativ).

APPLICATION

Low-pigment coating

In exterior applications, the requirement for weathering resistance requires applying two coats of low pigment coating. For the base and top coat, KEIM Concretal-Lasur may be diluted in any ratio with KEIM Concretal-Dilution (Fixativ) or KEIM Concretal-Base depending on the desired translucency of the finish. It is recommended to coat trial areas in order to determine the dilution ratio. Keep diluted KEIM Concretal-Lasur well stirred before and during work. Neither water nor any other materials may be added. It is important to work swiftly wet-in-wet and to maintain a wet edge to a corner or architectural feature.

Note: The system components Concretal-Lasur, Concretal- Base and Concretal-Dilution (Fixativ) can be mixed together in any desired ratio. KEIM Concretal-Base provides an attractive uniform transparency together with ideal application consistency and layer thickness. KEIM Concretal-Dilution (Fixativ) allows most translucent low-pigment finishes with brilliant colours and thin layer thickness.



COLORS FOREVER.



KEIM CONCRETAL LASUR

PACKAGING

1 gallon, 2 gallon and 4 gallon (packaged in a 5 gallon pail)

STORAGE

KEIM Concretal-Lasur, KEIM Concretal-Dilution (Fixativ) and KEIM Concretal-Base have a shelf life of 12 months in a closed container and under cool, frost-free conditions.

CLEANING OF TOOLS

Clean with water immediately after use.

DISPOSAL

EC Waste Code No. 08 01 12

Any residues must be emptied out of containers before recycling.

HAZARDOUS SUBSTANCES ORDINANCE CLASS

n/a

TRANSPORT HAZARD CLASS

n/a

Opaque coating

A base coat plus top coat are necessary in order to obtain an opaque protective coating which retains texture of the surface. this type of application requires 2 coats minimum with the first coat being diluted 10 - 25% with KEIM Concretal- Dilution (Fixativ) and the second coat applied undiluted by brush, roller or spraying, keeping a wet edge. It is important to work swiftly wet-in-wet and to maintain a wet edge to a corner or architectural feature.

COLOUR SHADE

Shades from KEIM Palette Exclusiv or a custom match to your colour selection within our natural mineral range.

APPLICATION CONDITIONS

Air and substrate temperature: >41°F up to max. 86°F (5°C 30°C) up to max. 80% relative humidity.

Apply only to dry surfaces and in dry weather. Do not apply under direct sun or on sun-heated substrates or in strong wind. Surfaces must be protected after application from rain, wind and direct sun until they are completely cured.

DRYING TIMES

At least 12 - 24 hours between coats.

If a pretreatment of one of the following water repellencies was applied allow drying before base coat is applied. Approx. 4 hours after KEIM Silangrund or 4-12 hours after KEIM Silan-100.

CONSUMPTION

The quantity of KEIM Concretal-Lasur and KEIM Concretal-Base or KEIM Concretal-Dilution (Fixativ) depends on the mixing ratio. A trial application using the tools and techniques for the final application may be required.


For an opaque finish

375-625 sq.ft./gallon undiluted

For a low-pigment finish

Stated values are for diluted ready to use material 375-625 sq.ft./gallon

The consumption values given are for guidance and depend on the desired translucency effect, application method and substrate condition. Exact values may only be determined by a trial application on site.



COLORS FOREVER.



KEIM CONCRETAL LASUR

CAUTION

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Product Code: M-SK 01

TECHNICAL DATA

DENSITY	1.20 g / cm ³
VOC'S ASTM D6886	<1 g / L (white and tinted)
VAPOUR DIFFUSION RESISTANCE	sd (H ₂ O) = <0.01 m
LIGHTFASTNESS OF COLOUR PIGMENT	A1 (Fb-Code acc. to BFS technical bulletin No. 26)
FLASH POINT	Non-flammable
VAPOUR PERMEABILITY	75 - 85 perms

DILUTION

A traduire?

Sur support non absorbant, appliquer le CONTACT PLUS non dilué.

Sur support absorbant, diluer au maximum avec 10 % de FIXATIF SPECIAL, de FIXATIF SOLDALIT ou FIXATIF CONCRETAL.

Ne jamais diluer à l'eau.

Note: The contents of this Technical Data Sheet are updated regularly. To ensure that you have the most recent version, please visit our website at the following address: www.king-masonry.com

This product is designed to meet the performance specifications outlined in this product Technical Data Sheet. If the product is used in conditions for which it was not intended, or applied in a manner contrary to the written recommendations contained in the product data sheet, the product may not reach such performance specifications. The foregoing is in lieu of any other warranties, representations or conditions, expressed or implied, including, but not limited to, implied warranties or conditions of merchantable quality or fitness for particular purposes, and those arising by statute or otherwise in law or from a course of dealing or usage of trade.

V1120

KING PACKAGED MATERIALS COMPANY

KPM Industries Ltd.
555 Michigan Dr., Suite 100
Oakville, ON L6L 0G4
Phone: 905-639-2993
Fax: 905-639-2997

Boisbriand Office
3825 rue Alfred-Laliberté
Boisbriand, QC J7H 1P7
Phone: 450-430-4104
Fax: 450-430-6855

Brantford Office
541 Oak Park Rd.
Brantford, ON N3T 5L8
Phone: 519-756-6177
Fax: 519-756-7490

Sudbury Office
644 Simmons Rd.
Dowling, ON POM 1R0
Phone: 705-855-1155
Fax: 705-855-1122